



TECHNICAL DATA SHEET

PVC TRIM SCREWS & PLUGS

PVC TRIM FASTENERS

FOR USE WITH OSI PVC TRIM SYSTEM

Description: OSI PVC Trim Fasteners are specifically designed to fasten cellular PVC trim to the home. It features the Cortex concealed fastening system that is virtually invisible providing the professional finish that homeowners expect. OSI fasteners offer the highest level of connection strength while also creating a consistently cored hole for the plug connection. The setting tool is engineered to ensure that the fasteners are set to the correct depth every time and attaches easily to the most popular drills. Each Universal PVC plug has been engineered to ensure ultimate long term performance against outdoor elements and will maintain long term durability under any conditions.

Available As:

Item #	Size	Color
1464016	1 box includes: 2 setting tools 150 2 3/4" screws 200 PVC plugs	001 White 005 White

Features & Benefits:

- For use with OSI PVC Trim System
- Cortex® Concealed Fastening System Offers Virtually Invisible Installation
- Highest Level of Connection Strength
- Setting Tool Ensures Fasteners are Set to Correct Depth
- Fast and Easy

Recommended For:

Designed to fasten cellular PVC trim to the home & fill holes

For Best Results:

- Test the Cortex system on a few trim boards to ensure you approve of the final look
- Use two fasteners at every framing member at 16" on center or less
- Use three fasteners if the board is wider than 8"
- To remove a fastener set below the trim surface, replace the setting tool in your impact driver with a #1 square bit, allowing full access to the seated fastener

Coverage:



The contents of one box will cover the installation of 100 linear feet of PVC trim board

Box Contents:

Setting Tools = 2

2 3/4" Screws = 150 pieces

PVC Plugs = 200





TECHNICAL DATA SHEET

Directions:

Installation Instructions:

1. Using a high voltage impact driver with the setting tool, drive the fastener to the pre-set level below the trim surface. The fastener must be driven perpendicular to the surface.
2. Place the plug into the hole with the trim surface side up and gently tap until it is flush with the trim. The cored hole must be free of debris or moisture

Tip: Ensure that the head of the fastener is flat with the trim surface to eliminate potential marring.

Important Information:

1. Under some conditions, you may see a subtle indication that there is a doweled plug in the trim. It is recommended that you test the Cortex™ system on a few trim boards to ensure you approve of the final look.
2. To remove a fastener set below the trim surface, replace the setting tool in your impact driver with a #1 square drive bit, allowing full access to the seated fastener.

Weathering:

PVC Trim Fasteners are made of cellular PVC trimboard and will weather to a similar shade. The weathering process may take a few weeks or months depending on the specific board and the intensity of sunlight.

General Fastening Pattern Guidelines:

Use two fasteners at every framing member at 16" on center or less. Use three fasteners if the board is wider than 8".

Limited Warranty:

This product is warranted to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty, express or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This limited warranty gives you specific legal rights, which vary from state to state. Henkel may be contacted at 1.800.624.7767 M-F 9:00 am to 4:00 pm ET for warranty assistance.

Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.



OSI Tougher than the Elements. For Professional Use Only. The Battle will be Fierce.

OSI works side by side with residential builders, contractors and remodeling professionals who use our products everyday on their jobsites. OSI combines this deep understanding with the sophisticated global innovation and manufacturing excellence of Henkel to make the world's best professional-grade caulks, sealants and adhesives.

1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET

www.ositough.com



OSI Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067

www.henkelna.com

Revision Date: 07/31/2014 Supercedes: 08/16/2010 Post Date: 07/31/2014